

AMENDMENTS TO THE CLAIMS

This listing of the claims will replace all prior versions, and listings, of claims in the application. Deleted material is shown in strike through, and inserted material is underlined, to show the changes made.

1-36. (Canceled).

1 37. (Currently Amended) A method of controlling a fluid flow rate of at least one pump and
2 an air flow rate of at least one fan, in a cooling system for cooling at least one device, the
3 method comprising the steps of:

4 providing a heat exchanger thermally coupled with the at least one device;

5 providing at least a portion of the heat exchanger with fluid from the at least one
6 pump, the fluid having the ability to absorb and store heat;

7 providing at least one temperature sensor coupled to the at least one device to
8 measure at least one temperature value of the at least one device;

9 receiving the at least one temperature value from the at least one temperature
10 sensor; and

11 providing a controller to selectively control at least one of the fluid flow rate and
12 the air flow rate, based on the at least one temperature value, such that the temperature of the at
13 least one device is maintained below a maximum allowable temperature.

1 38. (Original) The method of claim 37, wherein the fluid flows in a closed loop.

1 39. (Original) The method of claim 37, wherein the device comprises an electronic circuit.

1 40. (Original) The method of claim 39, wherein the electronic circuit is a microprocessor.

1 41. (Canceled).

1 42. (Currently Amended) The method of claim ~~[[41]]~~ 37, wherein the heat exchanger
2 contains internal flow regions for distributing fluid, and wherein the fluid [[medium]] is
3 [[laterally]] distributed through [[in]] the internal flow regions of the heat exchanger.

1 43. (Canceled).

1 44. (Withdrawn) The method of claim 41, wherein the at least one fan is maintained at a
2 constant maximum speed and the at least one pump is controlled such that the
3 temperature value of the device is maintained below a maximum allowable temperature
4 and acoustics transients are reduced below a given limit.

1 45. (Withdrawn) The method of claim 41, wherein the at least one fan is ramped up to a
2 maximum speed and the at least one pump is controlled such that the temperature value
3 of the device is maintained below a maximum allowable temperature and acoustic
4 transients are reduced below a given limit.

1 46. (Withdrawn) The method of claim 41, wherein the at least one fan is ramped down to a
2 minimum speed and the at least one pump is controlled such that the temperature value of
3 the device is maintained below a maximum allowable temperature and acoustic transients
4 are reduced below a given limit.

1 47. (Withdrawn) The method of claim 37, further including the step of providing at least one
2 current sensor coupled to the at least one device, to provide information which is
3 representative of current delivered to the at least one device and indicative of power
4 consumed by the at least one device, wherein the controller is coupled to receive the
5 information provided by the at least one current sensor.

1 48. (Withdrawn) The method of claim 37, further including the step of providing at least one
2 sensor measuring a pressure of the fluid at any position in the system, wherein the
3 controller is coupled to receive the information provided by the at least one sensor.

1 49. (Currently Amended) The method of claim [[37]] 108, wherein the at least one additional
2 temperature sensor measures temperature values of ambient air around the device.

1 50. (Currently Amended) The method of claim [[37]] 108, wherein the at least one additional
2 temperature sensor measures temperature values of the fluid at any point in the cooling
3 system.

- 1 51. (Withdrawn) The method of claim 37, wherein the controller adjusts a current supplied to
2 the at least one pump in response to the measured temperature value of the device.
- 1 52. (Withdrawn) The method of claim 37, wherein the controller adjusts a voltage supplied to
2 the at least one pump in response to the measured temperature value of the device.
- 1 53. (Withdrawn) The method of claim 37, wherein the controller adjusts a current supplied to
2 the at least one fan in response to the measured temperature value of the device.
- 1 54. (Withdrawn) The method of claim 37, wherein the controller adjusts a voltage supplied to
2 the at least one fan in response to the measured temperature value of the device.
- 1 55. (Withdrawn) The method of claim 37, wherein the controller adjusts an average power
2 supplied to the at least one fan with a pulse width modulated signal.
- 1 56. (Withdrawn) The method of claim 37, further including a valve for regulating the fluid
2 flow rate, which is selectively opened and closed to a variable state in response to the
3 measured temperature value.
- 1 57. (Withdrawn) The method of claim 37, wherein the at least one pump is controlled
2 independently of the at least one fan.
- 1 58. (Withdrawn) The method of claim 37, wherein the at least one pump is controlled
2 cooperatively with the at least one fan.
- 1 59. (Withdrawn) The method of claim 37, wherein a power consumption of the cooling
2 system is reduced to a minimal level by changing a power to the at least one pump and
the at least one fan.
- 1 60. (Withdrawn) The method of claim 37, wherein a noise of the at least one pump is held
2 constant while the at least one fan is used to control the temperature value of the device.

- 1
- 2
- 3

- 1 70. (Withdrawn) The method of claim 68, wherein the optimal control schemes include
2 increasing a fluid flow rate of the at least one pump, with a gradual increase of air flow
3 rate of the at least fan, so that acoustic noise variations are maintained below a
4 predetermined limit.
- 1 71. (Withdrawn) The method of claim 68, wherein the optimal control schemes include
2 gradually decreasing an air flow rate of the at least one fan such that acoustic noise
3 variations are maintained below a predetermined limit.
- 1 72. (Withdrawn) The method of claim 68, wherein the optimal control schemes include
2 decreasing a fluid flow rate of the at least one pump, with no increase of air flow rate of
3 the at least one fan.
- 73-107. (Canceled).
108. (New) The method of claim 37, wherein at least one additional temperature sensor
 measures at least one additional temperature value in the cooling system.
109. (New) The method of claim 42, wherein the internal flow regions comprise
 microchannels.